



APEX® 3300-85NT

Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Additive	Plasticizer				
Features	DEHP Plasticizer	Ethylene Oxide Sterilizable			
Uses	 Food Service Applications 	Medical/Healthcare Applications Tubing			
Appearance	Clear/Transparent				
Forms	• Pellets				
Processing Method	Extrusion				

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.23		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (100% Strain)	1560	psi	ASTM D638	
Tensile Strength (Break)	3000	psi	ASTM D638	
Tensile Elongation (Break)	390	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	85		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-9.40	°F	ASTM D746	
A delition of Information				

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B4 (0113827)

Clear Blue GB4 (0112948)

Clear Blue RB5 (1057907)

Clear Blue 1 (0707448)

Clear Blue 556 (1093815)

Clear Blue 703 (1093587)

Processing Information		
Extrusion	Nominal Value Unit	
Melt Temperature	360 °F	

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019