## +135-3858-6433 +188-1699-6168 +852-695-75415

## APEX<sup>®</sup> 3302-65VA-NT

TEKNOR APEX

Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

General Information				
Commercial: Active				
<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Medical/Healthcare Applic	ations			
Pellets				
	<ul> <li>Commercial: Active</li> <li>Africa &amp; Middle East</li> <li>Asia Pacific</li> <li>Medical/Healthcare Applic</li> </ul>	Commercial: Active     Africa & Middle East     Asia Pacific     Medical/Healthcare Applications		

----

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.19		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	1700	psi	ASTM D638	
Tensile Elongation (Break)	420	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	65		ASTM D2240	

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 5/1/2015

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.