



APEX® 33033RV-95NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

General Information						
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Features	BPA FreeE-beam SterilizableEthylene Oxide Sterilizable	 Latex Free No Animal Derived Components Non-Phthalate - TOTM Plasticizer 	 Non-Phthalate Plasticizer Radiation (Gamma) Resistant Radiation Sterilizable 			
Agency Ratings	• EC 1907/2006 (REACH)	 OEHHA (California) Proposition 65 				
RoHS Compliance	 RoHS Compliant 					
Forms	• Pellets					
Processing Method	Extrusion					

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.25		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (100% Strain)	2150	psi	ASTM D638	
Tensile Strength (Break)	3150	psi	ASTM D638	
Tensile Elongation (Break)	350	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A, 15 sec, Operating Stand	90			
Shore C, 10 sec, Hand Held	70			

Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

Bubble Tubing

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

TA Item 1138827

Notes

Revision Date: 6/17/2019

¹ Typical properties: these are not to be construed as specifications.