



## APEX® 33033RVA-80NT1 CBL B8 NP

## Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

	General Information				
General					
Material Status	Commercial: Active				
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Features	<ul><li>BPA Free</li><li>E-beam Sterilizable</li><li>Ethylene Oxide Sterilizable</li></ul>	<ul><li>Latex Free</li><li>No Animal Derived Components</li><li>Non-Phthalate - TOTM Plasticizer</li></ul>	<ul><li>Non-Phthalate Plasticizer</li><li>Radiation (Gamma) Resistant</li><li>Radiation Sterilizable</li></ul>		
Agency Ratings	• EC 1907/2006 (REACH)	OEHHA (California) Proposition 65			
RoHS Compliance	RoHS Compliant				
Forms	• Pellets				
Processing Method	<ul> <li>Extrusion</li> </ul>				

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.22		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (100% Strain)	1400	psi	ASTM D638	
Tensile Strength (Break)	2630	psi	ASTM D638	
Tensile Elongation (Break)	380	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A, 15 sec, Operating Stand	75			
Shore A, 15 sec, Hand Held	80			

## **Additional Information**

**EXAMPLE EXTRUSION APPLICATIONS** 

**Blood Pressure Tubing** 

**Blood Transport & Delivery** 

**Bubble Tubing** 

Cable Jacketing

Catheters

**Dialysis Tubing** 

**Drainage Tubing** 

**Endotracheal Airway Tubing** 

**Enteral Feeding Systems** 

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

## **Notes**

Revision Date: 5/30/201

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.