

## APEX® 33033RVA-85NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Tuesday, August 27, 2019

| General         |  |  |  |
|-----------------|--|--|--|
| Material Status | Commercial: Active   |  |  |
| Availability    | <ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>                          | <ul><li>Europe</li><li>Latin America</li></ul>   | North America  |
| Features        | <ul><li>BPA Free</li><li>E-beam Sterilizable</li><li>Ethylene Oxide Sterilizable</li></ul> | <ul> <li>Latex Free</li> <li>No Animal Derived Components</li> <li>Non-Phthalate - TOTM<br/>Plasticizer</li> </ul> | <ul> <li>Non-Phthalate Plasticizer</li> <li>Radiation (Gamma) Resistant</li> <li>Radiation Sterilizable</li> </ul> |
| Agency Ratings  | • EC 1907/2006 (REACH)   | <ul> <li>OEHHA (California) Proposition<br/>65</li> </ul>  | 1  |
| RoHS Compliance | RoHS Compliant   |  |  |
| Forms           | Pellets  |  |  |

**General Information** 

<u>+135-3858-6433</u> +188-1699-6168 +852-695-75415

| ASTM & ISO Properties <sup>1</sup> |               |      |             |  |
|------------------------------------|---------------|------|-------------|--|
| Physical                           | Nominal Value | Unit | Test Method |  |
| Density / Specific Gravity         | 1.22          |      | ASTM D792   |  |
| Mechanical                         | Nominal Value | Unit | Test Method |  |
| Tensile Strength (100% Strain)     | 1810          | psi  | ASTM D638   |  |
| Tensile Strength (Break)           | 3080          | psi  | ASTM D638   |  |
| Tensile Elongation (Break)         | 370           | %    | ASTM D638   |  |
| Hardness                           | Nominal Value | Unit | Test Method |  |
| Durometer Hardness                 |               |      | ASTM D2240  |  |
| Shore A, 15 sec, Operating Stand   | 82            |      |             |  |
| Shore A, 15 sec, Hand Held         | 85            |      |             |  |
| Additional Information             |               |      |             |  |
|                                    |               |      |             |  |

EXAMPLE EXTRUSION APPLICATIONS Blood Pressure Tubing Blood Transport & Delivery Bubble Tubing Cable Jacketing Catheters Dialysis Tubing Drainage Tubing Endotracheal Airway Tubing Enteral Feeding Systems Infusion Tubing Oxygen Tubing Peristaltic Pump Tubing Suction Tubing

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 6/10/2019

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.