



## **APEX® 3707-70LG-NT**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General Information				
General				
Material Status	<ul> <li>Commercial: Active</li> </ul>			
Availability	Africa & Middle East	• Europe	North America	
	<ul> <li>Asia Pacific</li> </ul>	<ul> <li>Latin America</li> </ul>		
Uses	Medical/Healthcare Applications			
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>			
Appearance	<ul> <li>Clear/Transparent</li> </ul>			
Forms	Pellets			

ASTM & ISO Properties <sup>1</sup>					
Physical	Nominal Value Un	it Test Method			
Density / Specific Gravity	1.22	ASTM D792			
Mechanical	Nominal Value Un	it Test Method			
Tensile Strength (Break)	2140 psi	ASTM D638			
Tensile Elongation (Break)	380 %	ASTM D638			
Hardness	Nominal Value Un	it Test Method			
Durometer Hardness (Shore A, 15 sec)	70	ASTM D2240			

## **Notes**

Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.