



## **APEX® 65010**

## Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General Information						
General						
Material Status	Commercial: Active					
Availability	Africa & Middle East	• Europe	North America			
	<ul> <li>Asia Pacific</li> </ul>	<ul> <li>Latin America</li> </ul>				
Uses	Wire & Cable Applications					
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>					
Appearance	Opaque					
Forms	Pellets					

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Density / Specific Gravity	1.38		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2950	psi	ASTM D638		
Tensile Elongation (Break)	360	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore C, 10 sec)	65		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	167	°F	ASTM D794		
Brittleness Temperature	-58.0	°F	ASTM D746		
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	32	%	ASTM D2863		

## **Notes**

Revision Date: 12/12/2013

<sup>&</sup>lt;sup>1</sup> Typical properties: these are not to be construed as specifications.