



APEX® 80128-Y

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

yyyy			110anoouaj, 71agaot 20, 2010			
General Information						
General						
Material Status	Commercial: Active					
Availability	Africa & Middle EastAsia Pacific	EuropeLatin America	North America			
Features	Sunlight Resistant (720 ho					
Uses	Cable Jacketing	 Insulation 				
Wire Types	• TW					
Agency Ratings	UL 1063UL 1581	• UL 62 • UL 83	• UL QMTT2			
RoHS Compliance	 RoHS Compliant 					
Appearance	Opaque					
Forms	• Pellets					

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Density / Specific Gravity	1.38		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2590	psi	ASTM D638		
Tensile Elongation (Break)	310	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	86		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	167	°F	ASTM D794		
Brittleness Temperature	-7.60	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity	3.2E+13	ohms∙cm	ASTM D257		
Dielectric Constant			ASTM D150		
1 kHz	5.01				
1 MHz	3.35				
Dissipation Factor			ASTM D150		
1 kHz	0.085				
1 MHz	0.069				
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	24	%	ASTM D2863		

Notes

Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.