



APEX® 80851-B

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

• Asia Pacific • Latin America Uses • Wire & Cable Applications • THHN • THWN • TW	
Availability • Africa & Middle East • Europe • Latin America Uses • Wire & Cable Applications • THHN • THWN • TW	
Availability • Asia Pacific • Latin America • Uses • Wire & Cable Applications • THHN • THWN • TW	
Wire Types • THHN • THWN • TW	North America
Wire Types • THW • TW	
A D III OMETE	
Agency Ratings • UL QMTT2	
RoHS Compliance • RoHS Compliant	
Appearance • Opaque	
Forms • Pellets	

ASTM & ISO Properties ¹			
Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.30		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	3300	psi	ASTM D638
Tensile Elongation (Break)	330	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec)	71		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	221	°F	ASTM D794
Brittleness Temperature	-27.4	°F	ASTM D746
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity (122°F)	3.0E+14	ohms·cm	ASTM D257
Dielectric Constant			ASTM D150
1 kHz	4.26		
1 MHz	3.01		
Dissipation Factor			ASTM D150
1 kHz	0.076		
1 MHz	0.053		
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	28	%	ISO 4589-2

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Natural (1012218)

Natural 14 (1016930)

Notes

Revision Date: 8/9/2019

¹ Typical properties: these are not to be construed as specifications.