



APEX® 84842

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

• •	, ,					
General Information						
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Features	High Heat Resistance	Sunlight Resistant (720	hours)			
Uses	Cable Jacketing	 Outdoor Applications 				
Wire Types	• CXTW • SJTW	SPT-1WSPT-2W	• STW • XTW			
Agency Ratings	• UL 62	• UL QMTT2				
RoHS Compliance	 RoHS Compliant 					
Appearance	• Opaque					
Forms	• Pellets					

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Density / Specific Gravity	1.33		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Break)	2600	psi	ASTM D638		
Tensile Elongation (Break)	360	%	ASTM D638		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore A, 15 sec)	86		ASTM D2240		
Thermal	Nominal Value	Unit	Test Method		
Continuous Use Temperature	221	°F	ASTM D794		
Brittleness Temperature	-22.0	°F	ASTM D746		
Electrical	Nominal Value	Unit	Test Method		
Volume Resistivity	1.6E+13	ohms·cm	ASTM D257		
Dielectric Constant			ASTM D150		
1 kHz	4.90				
1 MHz	3.06				
Dissipation Factor			ASTM D150		
1 kHz	0.096				
1 MHz	0.075				
Flammability	Nominal Value	Unit	Test Method		
Oxygen Index	29	%	ASTM D2863		

Notes

Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.