## <u>+135-3858-6433</u> +188-1699-6168 +852-695-75415

**General Information** 

## APEX® 96-A0097E-61

🚸 TEKNOR APEX

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

## **Product Description**

General					
Material Status	Commercial: Active				
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America		
Features	Low Gloss				
Uses	Automotive Exterior Parts				
Automotive Specifications	FORD WSK-M4D689-A7				
Forms	Pellets				
Processing Method	<ul> <li>Injection Molding</li> </ul>				

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.17		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	1660	psi	ASTM D638	
Tensile Elongation (Break)	440	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	61		ASTM D2240	

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.