



APEX® RE 8003

Teknor Apex Company - Rigid Polyvinyl Chloride

Tuesday, August 27, 2019

General Information					
General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	High Impact Resistance	Medium Gloss			
Appearance	Opaque				
Forms	Pellets				
Processing Method	Extrusion				

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.44		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Modulus	345000	psi	ASTM D638	
Tensile Strength (Yield)	6520	psi	ASTM D638	
Tensile Strength (Break)	6510	psi	ASTM D638	
Tensile Elongation (Yield)	3.1	%	ASTM D638	
Tensile Elongation (Break)	54	%	ASTM D638	
Flexural Modulus	389000	psi	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact			ASTM D256	
73°F, 0.125 in, Compression Molded	14	ft·lb/in		
Drop Impact Resistance ² (73°F, 0.125 in)	0.0230	in·lb/mil	ASTM D4226	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D, 10 sec)	80		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load			ASTM D648	
264 psi, Annealed, 0.125 in	157	°F		
Flammability	Nominal Value	Unit	Test Method	
Flame Rating (0.90 in)	• V-0 • 5VA		UL 94	

Additional Information

Performance Characteristics: Yellow Card, Interior, Medium Gloss, Excellent Finish

Notes

¹ Typical properties: these are not to be construed as specifications.

² Procedure B, 0.250" Conical Dart

Revision Date: 6/5/2019

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.