



APEX® RE 8219

Teknor Apex Company - Rigid Polyvinyl Chloride

Thursday, August 29, 2019

General Information						
General						
Material Status	Commercial: Active					
Availability	Africa & Middle East	• Europe	North America			
	 Asia Pacific 	 Latin America 				
Features	 Good Dimensional Stability 	High Impact Resistance				
	 Good Melt Strength 	 Medium Gloss 				
UL File NumberUSA	• QMFZ2 E54709					
Forms	Pellets					

ASTM & ISO Properties 1						
Physical		Nominal Value	Unit	Test Method		
Density / Specific Gravity		1.38		ASTM D792		
Mechanical		Nominal Value	Unit	Test Method		
Tensile Modulus		406000	psi	ASTM D638		
Tensile Strength (Break)		6130	psi	ASTM D638		
Flexural Modulus		399000	psi	ASTM D790		
Impact		Nominal Value	Unit	Test Method		
Notched Izod Impact (73°F, 0.125 in)		19	ft·lb/in	ASTM D256		
Hardness		Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D, 10 sec)		83		ASTM D2240		
Thermal		Nominal Value	Unit	Test Method		
Deflection Temperature Under Load				ASTM D648		
264 psi, Annealed, 0.125 in		160	°F			
Flammability		Nominal Value	Unit	Test Method		
Flame Rating						
	•	V-0		UL 94		
	•	5VA				
	•	V-0		CSA		
	•	5VA				

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Black 1 (1053928)

Grey 3187 (1054863)

Natural (1054835)

Tan 2216 (1113361)

Tan 2342 (1135075)

White 1458 (1068783)

Notes

Revision Date: 8/9/2019

¹ Typical properties: these are not to be construed as specifications.