



+135-3858-6433
+188-1699-6168
+852-695-75415

APEX® RE 9018A

Teknor Apex Company - Rigid Polyvinyl Chloride

Thursday, August 29, 2019

General Information

General

| | | | |
|-----------------|--|-----------------------------|-----------------|
| Material Status | • Commercial: Active | | |
| Availability | • Africa & Middle East • Asia Pacific | • Europe • Latin America | • North America |
| Forms | • Pellets | | |

ASTM & ISO Properties ¹

| Physical | Nominal Value | Unit | Test Method |
|---|---------------|------|-------------|
| Density / Specific Gravity | 1.44 | | ASTM D792 |
| Mechanical | Nominal Value | Unit | Test Method |
| Tensile Strength (Break) | 6000 | psi | ASTM D638 |
| Hardness | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore D, 15 sec, Hand Held) | 82 | | ASTM D2240 |

Additional Information

Data Sheet Applies to Color(s) Listed Below:
White 1407 (1072605)

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.