



# FLEXALLOY® 35022RV-60NT CBL B8 NP

# Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General Information				
General				
Material Status • Commercial: Active				
Availability  • Africa & Middle East • Asia Pacific	Europe     Latin America     North America			
<ul> <li>BPA Free</li> <li>E-beam Sterilizable</li> <li>Ethylene Oxide Sterilizable</li> </ul>	<ul> <li>Latex Free</li> <li>No Animal Derived Components</li> <li>Non-Phthalate Plasticizer</li> <li>Radiation (Gamma) Resistan</li> <li>Radiation Sterilizable</li> </ul>			
Agency Ratings • EC 1907/2006 (REACH)	OEHHA (California) Proposition     65			
RoHS Compliance • RoHS Compliant				
Forms • Pellets				
· · · · · · · · · · · · · · · · · · ·				

ASTM & ISO Properties <sup>1</sup>			
Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.20		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
50% Strain	375	psi	
100% Strain	650	psi	
300% Strain	1520	psi	
Tensile Strength (Break)	2090	psi	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Operating Stand	55		
Shore A. 15 sec. Hand Held	60		

Shore A, 15 sec, Hand Held

+135-3858-6433 +188-1699-6168 +852-695-75415

## FLEXALLOY® 35022RV-60NT CLL DO INF

## Teknor Apex Company - Flexible Polyvinyl Chloride

#### **Additional Information**

**EXAMPLE EXTRUSION APPLICATIONS** 

**Blood Pressure Tubing** 

**Blood Transport & Delivery** 

**Bubble Tubing** 

Cable Jacketing

Catheters

Dialysis Tubing

**Drainage Tubing** 

**Endotracheal Airway Tubing** 

**Enteral Feeding Systems** 

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

**Suction Tubing** 

### **EXAMPLE INJECTION MOLDING APPLICATIONS**

Adaptors

**Blood Pressure Bulbs** 

Canulae

Caps

Connectors

**Drip/Sight Chambers** 

Ear Protection

**Endotracheal Airway Cuffs** 

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136613)

Processing Information		
Extrusion	Nominal Value Unit	
Melt Temperature	350 to 365 °F	

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019