



**General Information** 

# FLEXALLOY® 35022RV-70NT CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General		
Material Status	Commercial: Active	
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	Europe     Latin America
Features	<ul><li>BPA Free</li><li>E-beam Sterilizable</li><li>Ethylene Oxide Sterilizable</li></ul>	<ul> <li>Latex Free</li> <li>No Animal Derived Components</li> <li>Non-Phthalate Plasticizer</li> <li>Radiation (Gamma) Resistant</li> <li>Radiation Sterilizable</li> </ul>
Agency Ratings	• EC 1907/2006 (REACH)	OEHHA (California) Proposition     65
RoHS Compliance	RoHS Compliant	
Forms	Pellets	
Processing Method	Extrusion	Injection Molding

ASTM & ISO Properties <sup>1</sup>				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.22		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength			ASTM D638	
50% Strain	540	psi		
100% Strain	895	psi		
300% Strain	1980	psi		
Tensile Strength (Break)	2300	psi	ASTM D638	
Tensile Elongation (Break)	360	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness			ASTM D2240	
Shore A, 15 sec, Operating Stand	65			
Shore A, 15 sec, Hand Held	70			

FLEXALLOY® 35022RV-70NT CbL DO INF

## Teknor Apex Company - Flexible Polyvinyl Chloride

#### Additional Information

EXAMPLE EXTRUSION APPLICATIONS Blood Pressure Tubing Blood Transport & Delivery Bubble Tubing Cable Jacketing Catheters Dialysis Tubing Drainage Tubing Endotracheal Airway Tubing Enteral Feeding Systems Infusion Tubing Oxygen Tubing Peristaltic Pump Tubing Suction Tubing

#### EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors **Blood Pressure Bulbs** Canulae Caps Connectors **Drip/Sight Chambers** Ear Protection Endotracheal Airway Cuffs Luers Mouthpieces Oxygen Masks Personal Safety Goggles **Resuscitation Bags** Suction Bulbs Syringe Bulbs Valves

Data Sheet Applies to Color(s) Listed Below: Clear Blue B8 NP (1136611)

### Processing Information

 Extrusion
 Nominal Value
 Unit

 Melt Temperature
 355 to 370
 °F

<u>+135-3858-6433</u> +188-1699-6168

#### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.