



## FLEXALLOY® 35022RV-75NT CBL B8 NP

## Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General Information			
General			
Material Status	Commercial: Active		
Availability	<ul><li> Africa &amp; Middle East</li><li> Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America
Features	<ul><li>BPA Free</li><li>E-beam Sterilizable</li><li>Ethylene Oxide Sterilizable</li></ul>	<ul><li>Latex Free</li><li>No Animal Derived Componer</li><li>Non-Phthalate - Citrate Plasticizer</li></ul>	<ul> <li>Non-Phthalate Plasticizer</li> <li>Radiation (Gamma) Resistant</li> <li>Radiation Sterilizable</li> </ul>
Agency Ratings	• EC 1907/2006 (REACH)	<ul> <li>OEHHA (California) Proposition</li> <li>65</li> </ul>	on
RoHS Compliance	<ul> <li>RoHS Compliant</li> </ul>		
Forms	• Pellets		
Processing Method	Electrostatic Spray Coating	Injection Molding	
	ASTM & ISO F	Properties <sup>1</sup>	
Physical		Nominal Value Unit	Test Method
Density / Specific Gravity		1.23	ASTM D792
Mechanical		Nominal Value Unit	Test Method
Tensile Strength			ASTM D638
50% Strain		665 psi	
100% Strain		1100 psi	
300% Strain		2330 psi	
Tensile Strength (Break)		2600 psi	ASTM D638
Tensile Elongation (Break)		350 %	ASTM D638
Hardness		Nominal Value Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Operating Stand		70	
Shore A, 15 sec, Hand Held		75	

+135-3858-6433 +188-1699-6168 +852-695-75415

## FLEXALLOY® 35022RV-75NT CLL DO INF

### Teknor Apex Company - Flexible Polyvinyl Chloride

#### **Additional Information**

**EXAMPLE EXTRUSION APPLICATIONS** 

**Blood Pressure Tubing** 

**Blood Transport & Delivery** 

**Bubble Tubing** 

Cable Jacketing

Catheters

Dialysis Tubing

**Drainage Tubing** 

**Endotracheal Airway Tubing** 

**Enteral Feeding Systems** 

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

**Suction Tubing** 

#### **EXAMPLE INJECTION MOLDING APPLICATIONS**

Adaptors

**Blood Pressure Bulbs** 

Canulae

Caps

Connectors

Drip/Sight Chambers

Ear Protection

**Endotracheal Airway Cuffs** 

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

**Extrusion** 

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136610)

# Processing Information Nominal Value Unit

Melt Temperature 360 to 375 °F

#### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019