



General Information

FLEXALLOY® 35022RV-80NT CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

| General | | |
|-------------------|--|--|
| Material Status | Commercial: Active | |
| Availability | Africa & Middle East Asia Pacific | Europe Latin America |
| Features | BPA FreeE-beam SterilizableEthylene Oxide Sterilizable | Latex Free No Animal Derived Components Non-Phthalate - Citrate Plasticizer Non-Phthalate - Citrate Radiation Sterilizable |
| Agency Ratings | • EC 1907/2006 (REACH) | OEHHA (California) Proposition 65 |
| RoHS Compliance | RoHS Compliant | |
| Forms | Pellets | |
| Processing Method | Extrusion | Injection Molding |

| ASTM & ISO Properties ¹ | | | | |
|------------------------------------|---------------|------|-------------|--|
| Physical | Nominal Value | Unit | Test Method | |
| Density / Specific Gravity | 1.24 | | ASTM D792 | |
| Mechanical | Nominal Value | Unit | Test Method | |
| Tensile Strength | | | ASTM D638 | |
| 50% Strain | 890 | psi | | |
| 100% Strain | 1400 | psi | | |
| 300% Strain | 2610 | psi | | |
| Tensile Strength (Break) | 2820 | psi | ASTM D638 | |
| Tensile Elongation (Break) | 340 | % | ASTM D638 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Durometer Hardness | | | ASTM D2240 | |
| Shore A, 15 sec, Operating Stand | 75 | | | |
| Shore A, 15 sec, Hand Held | 80 | | | |

FLEXALLOY® 35022RV-80NT CbL DO INF

Teknor Apex Company - Flexible Polyvinyl Chloride

Additional Information

EXAMPLE EXTRUSION APPLICATIONS Blood Pressure Tubing Blood Transport & Delivery Bubble Tubing Cable Jacketing Catheters Dialysis Tubing Drainage Tubing Endotracheal Airway Tubing Enteral Feeding Systems Infusion Tubing Oxygen Tubing Peristaltic Pump Tubing Suction Tubing

EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors **Blood Pressure Bulbs** Canulae Caps Connectors **Drip/Sight Chambers** Ear Protection Endotracheal Airway Cuffs Luers Mouthpieces Oxygen Masks Personal Safety Goggles **Resuscitation Bags** Suction Bulbs Syringe Bulbs Valves

Data Sheet Applies to Color(s) Listed Below: Clear Blue B8 NP (1136609)

Processing Information

 Extrusion
 Nominal Value
 Unit

 Melt Temperature
 365 to 380
 °F

<u>+135-3858-6433</u> +188-1699-6168

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.