



FLEXALLOY® 35033RV-50NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General Information			
General			
Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America
Features	BPA FreeE-beam SterilizableEthylene Oxide Sterilizable	Latex FreeNo Animal Derived ComponerNon-Phthalate - TOTM Plasticizer	 Non-Phthalate Plasticizer Radiation (Gamma) Resistant Radiation Sterilizable
Agency Ratings	• EC 1907/2006 (REACH)	 OEHHA (California) Proposition 65 	on
RoHS Compliance	 RoHS Compliant 		
Forms	• Pellets		
Processing Method	• Extrusion	Injection Molding	
	ASTM & ISO F	Properties ¹	
Physical		Nominal Value Unit	Test Method
Density / Specific Gravity		1.12	ASTM D792
Mechanical		Nominal Value Unit	Test Method
Tensile Strength			ASTM D638
50% Strain		230 psi	
100% Strain		420 psi	
300% Strain		1030 psi	
Tensile Strength (Break)		1430 psi	ASTM D638
Tensile Elongation (Break)		420 %	ASTM D638
Hardness		Nominal Value Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Operating Stand		45	
Shore A, 15 sec, Hand Held		50	

+135-3858-6433 +188-1699-6168 +852-695-75415

FLEXALLOY® 35033RV-50NT1 CDL DO INF

Teknor Apex Company - Flexible Polyvinyl Chloride

Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

Bubble Tubing

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors

Blood Pressure Bulbs

Canulae

Caps

Connectors

Drip/Sight Chambers

Ear Protection

Endotracheal Airway Cuffs

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136626)

Processing Information Extrusion Nominal Value Unit Melt Temperature 345 to 360 °F

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019