



FLEXALLOY® 35033RV-70NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

Wednesday, August 28, 2019

General Information			
General			
Material Status	Commercial: Active		
Availability	 Africa & Middle East Asia Pacific	EuropeLatin AmericaNorth America	
Features	BPA FreeE-beam SterilizableEthylene Oxide Sterilizable	 Latex Free No Animal Derived Components Non-Phthalate Plasticizer Radiation (Gamma) Resistant Plasticizer 	
Agency Ratings	• EC 1907/2006 (REACH)	 OEHHA (California) Proposition 65 	
RoHS Compliance	 RoHS Compliant 		
Forms	• Pellets		
Processing Method	• Extrusion	Injection Molding	
	ASTM & ISO F	Properties ¹	
Physical		Nominal Value Unit	t Test Method
Density / Specific Gravity		1.18	ASTM D792
Mechanical		Nominal Value Unit	t Test Method
Tensile Strength			ASTM D638
50% Strain		555 psi	
100% Strain		935 psi	
300% Strain		2000 psi	
Tensile Strength (Break)		2300 psi	ASTM D638
Tensile Elongation (Break)		360 %	ASTM D638
Hardness		Nominal Value Unit	t Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Operating Stand		65	
Shore A, 15 sec, Hand Held		70	

+135-3858-6433 +188-1699-6168 +852-695-75415

FLEXALLOY® 35033RV-70NT1 CDL DO INF

Teknor Apex Company - Flexible Polyvinyl Chloride

Additional Information

EXAMPLE EXTRUSION APPLICATIONS

Blood Pressure Tubing

Blood Transport & Delivery

Bubble Tubing

Cable Jacketing

Catheters

Dialysis Tubing

Drainage Tubing

Endotracheal Airway Tubing

Enteral Feeding Systems

Infusion Tubing

Oxygen Tubing

Peristaltic Pump Tubing

Suction Tubing

EXAMPLE INJECTION MOLDING APPLICATIONS

Adaptors

Blood Pressure Bulbs

Canulae

Caps

Connectors

Drip/Sight Chambers

Ear Protection

Endotracheal Airway Cuffs

Luers

Mouthpieces

Oxygen Masks

Personal Safety Goggles

Resuscitation Bags

Suction Bulbs

Syringe Bulbs

Valves

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B8 NP (1136622)

Processing Information Extrusion Nominal Value Unit Melt Temperature 355 to 370 °F

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 8/9/2019