



FLEXALLOY® 9300-65

Teknor Apex Company - Polyvinyl Chloride Elastomer

Saturday, August 24, 2019

General Information					
General					
Material Status	Commercial: Active				
Availability	Africa & Middle EastAsia Pacific	EuropeLatin America	North America		
Features	 Good Thermal Stability Oil Resistant	Recyclable MaterialUltra High Molecular Weight	Weather Resistant		
Uses	Coating ApplicationsHose	SealsTool/Tote Box	• Tubing		
Forms	• Pellets				
Processing Method	• Extrusion	Injection Molding			

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.23		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	2400	psi	ASTM D638	
Tensile Elongation (Break)	330	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A, 15 sec)	65		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Continuous Use Temperature	221	°F	ASTM D794	
Brittleness Temperature	-47.2	°F	ASTM D746	

Notes

Revision Date: 12/12/2013

¹ Typical properties: these are not to be construed as specifications.