



FLEXALLOY® 9602-72

Teknor Apex Company - Polyvinyl Chloride Elastomer

Saturday, August 24, 2019

General Information						
General						
Material Status	Commercial: Active					
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America			
Features	Flame RetardantHigh Heat Resistance	Low Temperature FlexibilitySunlight Resistant (720 hours)				
Uses	 Cable Jacketing 					
Wire Types	• SEOW • SEW	• SJEOW • SJEW	• STEOW • STEW			
Agency Ratings	UL Class 11UL Class 12	UL Class 36UL Class 43	• UL QMTT2			
RoHS Compliance	 RoHS Compliant 					
Appearance	Opaque					
Forms	Pellets					

Density / Specific Gravity 1.25 ASTM D792 Mechanical Nominal Value Unit Test Method Tensile Strength (Break) 2100 psi ASTM D638 Tensile Elongation (Break) 330 % ASTM D638 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A, 15 sec) 72 ASTM D2240 Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant ASTM D150 ASTM D150 1 kHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150	ASTM & ISO Properties 1					
Mechanical Nominal Value Unit Test Method Tensile Strength (Break) 2100 psi ASTM D638 Tensile Elongation (Break) 330 % ASTM D638 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A, 15 sec) 72 ASTM D2240 Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant 6.19 ASTM D150 1 kHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 MHz 0.10 Test Method	Physical	Nominal Value	Unit	Test Method		
Tensile Strength (Break) 2100 psi ASTM D638 Tensile Elongation (Break) 330 % ASTM D638 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A, 15 sec) 72 ASTM D2240 Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant ASTM D150 ASTM D150 1 kHz 6.19 ASTM D150 1 kHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 MHz 0.10 Test Method	Density / Specific Gravity	1.25		ASTM D792		
Tensile Elongation (Break) 330 % ASTM D638 Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A, 15 sec) 72 ASTM D2240 Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant 6.19 ASTM D150 1 kHz 6.19 ASTM D150 1 kHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.10 Test Method	Mechanical	Nominal Value	Unit	Test Method		
Hardness Nominal Value Unit Test Method Durometer Hardness (Shore A, 15 sec) 72 ASTM D2240 Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method 1 kHz 6.19 ASTM D150 1 kHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 Test Method 1 kHz 0.10 Test Method	Tensile Strength (Break)	2100	psi	ASTM D638		
Durometer Hardness (Shore A, 15 sec) 72 ASTM D2240 Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Diselectric Constant 6.19 ASTM D150 1 kHz 6.19 ASTM D150 1 kHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.10 Test Method	Tensile Elongation (Break)	330	%	ASTM D638		
Thermal Nominal Value Unit Test Method Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant 6.19 ASTM D150 1 kHz 4.08 ASTM D150 Dissipation Factor ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 Test Method 1 MHz Nominal Value Unit Test Method	Hardness	Nominal Value	Unit	Test Method		
Continuous Use Temperature 221 °F ASTM D794 Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant ASTM D150 1 kHz 6.19 ASTM D150 1 MHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 MHz 0.10 Test Method	Durometer Hardness (Shore A, 15 sec)	72		ASTM D2240		
Brittleness Temperature -58.0 °F ASTM D746 Electrical Nominal Value Unit Test Method Dielectric Constant ASTM D150 1 kHz 6.19 ASTM D150 1 MHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 MHz 0.10 Test Method	Thermal	Nominal Value	Unit	Test Method		
Electrical Nominal Value Unit Test Method Dielectric Constant ASTM D150 1 kHz 6.19 ASTM D150 1 MHz 4.08 ASTM D150 1 kHz 0.12 ASTM D150 1 kHz 0.12 ASTM D150 1 MHz 0.10 Test Method	Continuous Use Temperature	221	°F	ASTM D794		
Dielectric Constant ASTM D150 1 kHz 6.19 1 MHz 4.08 Dissipation Factor ASTM D150 1 kHz 0.12 1 MHz 0.10 Flammability Nominal Value Unit Test Method	Brittleness Temperature	-58.0	°F	ASTM D746		
1 kHz 6.19 1 MHz 4.08 Dissipation Factor ASTM D150 1 kHz 0.12 1 MHz 0.10 Flammability Nominal Value Unit Test Method	Electrical	Nominal Value	Unit	Test Method		
1 MHz 4.08 Dissipation Factor ASTM D150 1 kHz 0.12 1 MHz 0.10 Flammability Nominal Value Unit Test Method	Dielectric Constant			ASTM D150		
Dissipation Factor ASTM D150 1 kHz 0.12 1 MHz 0.10 Flammability Nominal Value Unit Test Method	1 kHz	6.19				
1 kHz 0.12 1 MHz 0.10 Flammability Nominal Value Unit Test Method	1 MHz	4.08				
1 MHz 0.10 Flammability Nominal Value Unit Test Method	Dissipation Factor			ASTM D150		
Flammability Nominal Value Unit Test Method	1 kHz	0.12				
	1 MHz	0.10				
Oxygen Index 26 % ASTM D2863	Flammability	Nominal Value	Unit	Test Method		
	Oxygen Index	26	%	ASTM D2863		

Notes

Revision Date: 11/3/2014

¹ Typical properties: these are not to be construed as specifications.