<u>+135-3858-6433</u> +188-1699-6168 +852-695-75415

Sinvicomp DBS2006

Teknor Apex Asia Pacific PTE. LTD. - Rigid Polyvinyl Chloride

Thursday, August 29, 2019

General		
Material Status	Commercial: Active	
Availability	Asia Pacific	
Features	High Impact Resistance	
Uses	Piping	
RoHS Compliance	RoHS Compliant	
Forms	Powder	
Processing Method	Extrusion	

ASTM & ISO Properties¹

Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.40		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Break)	7110	psi	ASTM D638	
Tensile Elongation ² (Break)	150	%	ASTM D638	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	8.3	ft·lb/in	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Vicat Softening Temperature	176	°F	ASTM D1525	
Thermal Stability ³ (374°F)	> 30	min	BS 2782	

Notes

¹ Typical properties: these are not to be construed as specifications.

² 20 in/min

³ Congo Red

Revision Date: 3/12/2014

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.