<u>+135-3858-6433</u> +188-1699-6168 +852-695-75415

Sinvicomp DBS3604

Teknor Apex Asia Pacific PTE. LTD. - Rigid Polyvinyl Chloride

Thursday, August 29, 2019

General Information

General	
Material Status	Commercial: Active
Availability	Asia Pacific
Features	Good Impact Resistance
Uses	Electrical/Electronic Applications
Forms	Powder
Processing Method	Extrusion

ASTM & ISO Properties ¹					
Physical	Nominal Value	Unit	Test Method		
Density / Specific Gravity	1.39		ASTM D792		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	7110	psi	ASTM D638		
Tensile Elongation (Break)	80	%	ASTM D638		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact	1.8	ft·lb/in	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		
Vicat Softening Temperature	210	°F	ASTM D1525 ²		
Heat Stability ³ (374°F)	> 30.0		BS 2782		
Notes					
¹ Typical properties: these are not to be construed as specifications.					

² Loading 1 (10 N)

³ Congo Red

Revision Date: 1/1/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.