<u>+135-3858-6433</u> +188-1699-6168 +852-695-75415

Sinvicomp SIF5166

Teknor Apex Asia Pacific PTE. LTD. - Flexible Polyvinyl Chloride

Thursday, August 29, 2019

General Information

General	
Material Status	Commercial: Active
Availability	Asia Pacific
Features	High Stiffness
Uses	Wire & Cable Applications
Forms	Pellets
Processing Method	Extrusion

ASTM & ISO Properties ¹				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.56		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Yield)	2470	psi	ASTM D638	
Tensile Elongation ² (Break)	190	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	91		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Thermal Stability ³ (374°F)	> 1	hr	BS 2782	
Aging	Nominal Value	Unit	Test Method	
Change in Tensile Strength (176°F, 168 hr)	10	%	ASTM D638	
Change in Ultimate Elongation (176°F, 168 hr)	15	%	ASTM D638	
Electrical	Nominal Value	Unit	Test Method	
Volume Resistivity (68°F)	1.0E+14	ohms∙cm	BS 2782	

Notes

¹ Typical properties: these are not to be construed as specifications.

² 9.8 in/min

³ Congo Red

Revision Date: 1/2/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.