



Sinvicomp SRF1707S

Teknor Apex Asia Pacific PTE. LTD. - Rigid Polyvinyl Chloride

Thursday, August 29, 2019

General Information

Product Description

"Sinvicomp" SRF 1707S is an injection molding grade polyvinylchloride compound available in pellet form. SRF 1707S provides normal impact performance suitable for rigid pipes fittings, electrical sockets and couplings.

General	
Material Status	Commercial: Active
Availability	Asia Pacific
Features	Medium Impact Resistance
Uses	Electrical Parts Fittings
Forms	• Pellets
Processing Method	Injection Molding

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.48		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	6540	psi	ASTM D638	
Tensile Elongation (Break)	110	%	ASTM D638	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	1.6	ft·lb/in	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Vicat Softening Temperature	199	°F	ASTM D1525	
Heat Stability - (Congo Red @190°C)	30.0	min	BS 2782	

Additional Information

Typical temperature profile for processing SINVICOMP compound is from 160oC to 180oC. The optimum temperatures depend on the type of machine as well as screw design being used to process SINVICOMP.

Notes

Revision Date: 7/23/2018

¹ Typical properties: these are not to be construed as specifications.