

# VIDUX™ CV-92-A5008A-91 BLACK

Teknor Apex Company - Flexible Polyvinyl Chloride

Thursday, August 29, 2019

## General Information

### General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Additive	• Antistatic	• Plasticizer	
Features	• Antistatic • Conductive	• Electromagnetic Shielding (EMI) • Ethylene Oxide Sterilizable	• Non-DEHP Plasticizer • Radio Frequency Shielding (RFI)
Uses	• Coating Applications • Coaxial Cable Jacketing	• Electronic Cable Jacketing • Wire & Cable Applications	
RoHS Compliance	• RoHS Compliant		
Appearance	• Black		
Forms	• Pellets		
Processing Method	• Extrusion		

## ASTM & ISO Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.29		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	1200	psi	ASTM D638
Tensile Elongation (Break)	80	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec	91		
Shore C, 10 sec	66		
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	2.5	ohms·cm	ASTM D257
Conductivity	4.0	ohms·cm	ASTM D257

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

Revision Date: 12/12/2013

The information and recommendations contained in this bulletin are, to the best of our knowledge, accurate and reliable but no guarantee of their accuracy is made. All products are sold upon condition that purchasers shall make their own tests to determine the suitability of such products for their particular purposes and uses and purchasers assume all risks and liability for the results of use of the products, including use in accordance with seller's recommendations. Nothing in this bulletin constitutes permission or a recommendation to practice or use any invention covered by any patent owned by this company or by others. There is no warranty of merchantability and there are no other warranties for the products described.