



Vital-Line SHE6000

Teknor Apex Asia Pacific PTE. LTD. - Flexible Polyvinyl Chloride

Thursday, August 29, 2019

General Information

Product Description

Vital-Line SHE 6000 is a Polyvinyl Chloride Medical Extrusion Compound available in pellet form. It provides Good ETO Stability performance suitable for Medical Devices.

General			
Material Status	Commercial: Active		
Availability	Asia Pacific		
Features	DEHP Plasticizer Ethylene Oxide Sterilizable		
Uses	Medical/Healthcare Applications		
Forms	• Pellets		
Processing Method	Extrusion		

ASTM & ISO Properties 1

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.20		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ² (Yield)	1890	psi	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	67		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Heat Stability (374°F)	> 30.0	min	ASTM D2115-92

Additional Information

Typical temperature profile for processing compounding is from 135°C to 180°C. The optimum temperatures depend on the type of machine as well as screw design being used to process.

Feeding zone: 135°C

Compression zone: 145°C to 155°C Mixing zone: 155°C to 170°C Nozzle/Die zone: 160°C to 180°C

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 9/18/2016

² 20 in/min