



Vital-Line SHM4200

Teknor Apex Asia Pacific PTE. LTD. - Flexible Polyvinyl Chloride

Thursday, August 29, 2019

| General Information | | | | |
|---------------------|---------------------------------|--|--|--|
| General | | | | |
| Material Status | Commercial: Active | | | |
| Availability | Asia Pacific | | | |
| Features | Ethylene Oxide Sterilizable | | | |
| Uses | Medical/Healthcare Applications | | | |
| Forms | • Pellets | | | |
| Processing Method | Injection Molding | | | |

| ASTM & ISO Properties 1 | | | | | |
|---------------------------------------|----------------|------|---------------|--|--|
| Physical | Nominal Value | Unit | Test Method | | |
| Density / Specific Gravity | 1.22 | | ASTM D792 | | |
| Mechanical | Nominal Value | Unit | Test Method | | |
| Tensile Strength ² (Yield) | 2030 | psi | ASTM D638 | | |
| Tensile Elongation (Break) | • 280 • 250 | % | ASTM D638 | | |
| Hardness | Nominal Value | Unit | Test Method | | |
| Shore Hardness (Shore A) | 73 | | ASTM D2240 | | |
| Thermal | Nominal Value | Unit | Test Method | | |
| Heat Stability ³ (374°F) | > 30.0 | min | ASTM D2115-92 | | |

Notes

Revision Date: 10/7/2014

¹ Typical properties: these are not to be construed as specifications.

² 20 in/min

³ Congo Red