



Vital-Line SHM4500

Teknor Apex Asia Pacific PTE. LTD. - Flexible Polyvinyl Chloride

Thursday, August 29, 2019

| General Information | | |
|---------------------|---------------------------------|--|
| General | | |
| Material Status | Commercial: Active | |
| Availability | Asia Pacific | |
| Features | Ethylene Oxide Sterilizable | |
| Uses | Medical/Healthcare Applications | |
| Forms | • Pellets | |
| Processing Method | Injection Molding | |

| ASTM & ISO Properties 1 | | | | |
|---|---------------|------|---------------|--|
| Physical | Nominal Value | Unit | Test Method | |
| Density / Specific Gravity | 1.22 | | ASTM D792 | |
| Mechanical | Nominal Value | Unit | Test Method | |
| Tensile Strength ² | 1740 | psi | ASTM D638 | |
| Tensile Elongation ² (Break) | 260 | % | ASTM D638 | |
| Hardness | Nominal Value | Unit | Test Method | |
| Durometer Hardness (Shore A) | 72 | | ASTM D2240 | |
| Thermal | Nominal Value | Unit | Test Method | |
| Heat Stability (374°F) | > 30.0 | | ASTM D2115-92 | |
| | | | | |

Notes

Revision Date: 6/21/2015

¹ Typical properties: these are not to be construed as specifications.

² 20 in/min