



Vital-Line SHM8505

Teknor Apex Asia Pacific PTE. LTD. - Flexible Polyvinyl Chloride

Thursday, August 29, 2019

General Information				
Product Description				
Vital-Line SHM 8505 is a Polyv	inyl Chloride Medical Molding Compound available in pellet form.			
General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Features	Ethylene Oxide Sterilizable Non-Phthalate Plasticizer			
Uses	Medical/Healthcare Applications			
Forms	• Pellets			
Processing Method	Injection Molding			

ASTM & ISO Properties 1				
Physical	Nominal Value	Unit	Test Method	
Density / Specific Gravity	1.16		ASTM D792	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ² (Yield)	1160	psi	ASTM D638	
Tensile Elongation (Break)	320	%	ASTM D638	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore A)	50		ASTM D2240	
Thermal	Nominal Value	Unit	Test Method	
Heat Stability (374°F)	> 30.0	min	ASTM D2115-92	

Additional Information

Typical temperature profile for processing compound is from 130oC to 160oC. The optimum temperatures depend on the type of machine as well as screw design being used to process.

Feeding zone 130°C Compression zone 135°C \sim 155°C Nozzle / Die zone 140°C \sim 160°C Mold temperature 0°C \sim 50°C

Notes

¹ Typical properties: these are not to be construed as specifications.

Revision Date: 7/23/2018

² 20 in/min