



Sinpolene MBB1512

Teknor Apex Asia Pacific PTE. LTD. - Low Density Polyethylene

General Information

Product Description

SINPOLENE MBB1512 is a masterbatch based on a medium jetness carbon black dispersed in polyethylene. It is designed specifically for use in tubular film blowing, blow moulding, extrusion and injection molding of polyolefins. The ingredients used in MBB1512 are approved by most regulations governing the contact of materials with food.

SINPOLENE MBB1512 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Good weather and UV light protection
- * Minimal wear effect on processing equipment

General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Asia Pacific
Additive	• Carbon Black: 35%
Features	• General Purpose
Uses	• Non-specific Food Applications
RoHS Compliance	• RoHS Compliant
Appearance	• Black
Forms	• Pellets
Processing Method	• Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.14		ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	10 to 30	g/10 min	ASTM D1238
Carbon Black Content	35	%	ASTM D1603
Moisture Content	< 0.25	%	ASTM D3030

Additional Information

Recommended dosage: 1 - 3%

Notes

¹ Typical properties: these are not to be construed as specifications.