+135-3858-6433 (GuangDong) +188-1699-6168 (ShangHai) +852-6957-5415 (HongKong)



Sinpolene MBW0442

Teknor Apex Asia Pacific PTE. LTD. - Low Density Polyethylene

General Information

Product Description

Sinpolene MBW0442 is a LDPE-base pure white masterbatch designed specifically for use in tubular film blowing, blow moulding and extrusion of polyolefins. Sinpolene MBW0442 contains extender which gives anti-blocking properties. Sinpolene MBW0442 offers high colouring value with excellent quality and performance.

The white undertone of this masterbatch is attributed by specially selected high performance, fine crystal size rutile titanium dioxide.

Sinpolene MBW0442 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High opacifying power
- * Excellent whiteness

General				
Material Status	Commercial: Active			
Availability	Asia Pacific			
Filler / Reinforcement	Titanium Dioxide, 60% Filler by Weight			
Uses	• Film	 Masterbatch 	• Sheet	
RoHS Compliance	 RoHS Compliant 			
Appearance	• White			
Forms	• Pellets			
Processing Method	Blown Film	 Sheet Extrusion 		

Physical	Nominal Value Unit	Test Method
Density / Specific Gravity	1.76	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	< 15 g/10 min	ASTM D1238
Moisture Content	< 0.20 %	ASTM D3030

Recomended dosage: 2 - 5%

Notes

¹ Typical properties: these are not to be construed as specifications.