



# Sinpolene MBB2401

Teknor Apex Asia Pacific PTE. LTD. - Linear Low Density Polyethylene

## General Information

### Product Description

SINPOLENE MBB2401 is a modified copolymer based black masterbatch designed specifically for use in injection moulding, tubular film blowing, blow moulding and extrusion of polyolefins. SINPOLENE MBB2401 has high pigment loading and thus offers high coloring value with superior quality and performance.

SINPOLENE MBB2401 is delivered as free flowing pellets for processing convenience.

### CHARACTERISTICS

- \* Easy processing
- \* Good dispersion
- \* High jetness
- \* Minimal wear effect on processing equipment

### General

Material Status	• Commercial: Active		
Availability	• Asia Pacific		
Features	• General Purpose		
Uses	• Film	• Sheet	
RoHS Compliance	• RoHS Compliant		
Forms	• Pellets		
Processing Method	• Blown Film	• Sheet Extrusion	

## ASTM & ISO Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.16		ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/10.0 kg)	< 30	g/10 min	ASTM D1238
Carbon Black Content	40	%	ASTM D1603
Moisture Content	< 0.25	%	ASTM D3030

### Additional Information

Recommended dosage: 2 - 5%

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.