+135-3858-6433 (GuangDong) +188-1699-6168 (ShangHai) +852-6957-5415 (HongKong)



Sinpolene MBW3291

Teknor Apex Asia Pacific PTE. LTD. - Linear Low Density Polyethylene

General Information

Product Description

Sinpolene MBW3291 is a polyethylene-based pure white masterbatch designed specifically for use in tubular film blowing, blow moulding and coextrusion of polyolefins. With its high pigment loading, Sinpolene MBW3291 offers high colouring value with excellent quality and performance.

The blue undertone of this masterbatch is attributed by specially selected high performance, fine crystal size rutile titanium dioxide.

Sinpolene MBW34291 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High opacifying power
- * Excellent whiteness
- * Good weathering resistant

General		
Material Status	Commercial: Active	
Availability	Asia Pacific	
Filler / Reinforcement	Titanium Dioxide, 70% Filler by Weight	
Features	General Purpose Good Weather Resistance	
Uses	• Film	
Forms	Pellets	
Processing Method	Blown Film	

Physical	Nominal Value Unit	Test Method
Density / Specific Gravity	2.00	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	30 to 60 g/10 min	ASTM D1238
Moisture Content	< 0.20 %	ASTM D3030

Recommeded dosage 5 - 10%

Notes

¹ Typical properties: these are not to be construed as specifications.