

Sinpolene MBB1501

Teknor Apex Asia Pacific PTE. LTD. - Polyethylene

General Information

Product Description

SINPOLENE MBB 1501 is a Polyolefin based black masterbatch designed specifically for use in injection moulding, compounding and extrusion of polyolefins, polystyrene and ABS.

SINPOLENE MBB1501 has high pigment loading and thus offers high jetness with superior quality and performance.

SINPOLENE MBB 1501 is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High jetness
- * Minimal wear effect on processing equipment

General Material Status · Commercial: Active Availability Asia Pacific Features · Recyclable Material • Compounding Masterbatch Uses **RoHS** Compliance · RoHS Compliant Black Appearance Forms · Pellets • Compounding Injection Molding **Processing Method**

ASTM & ISO Properties ¹		
Physical	Nominal Value Unit	Test Method
Density / Specific Gravity	1.19	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	15 to 60 g/10 min	ASTM D1238
Carbon Black Content	47 %	ASTM D1603
Moisture Content	< 0.25 %	ASTM D3030

Recommended dosage: 1 - 3%

Notes

¹ Typical properties: these are not to be construed as specifications.