



# APEX® 23-A7428B-85

Teknor Apex Company - Flexible Polyvinyl Chloride

## General Information

### General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Asia Pacific • Latin America • North America
Features	• Fungus Resistant • General Purpose • Medium Gloss • UV Resistant
Uses	• Profiles
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Forms	• Pellets
Processing Method	• Extrusion

## ASTM & ISO Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.46		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	1890	psi	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Operating Stand	77		
Shore A, 15 sec, Hand Held	85		

### Additional Information

Data Sheet applies to color(s) listed below:

Natural (1006527)

White 1 (1006572)

04/2024-dmm

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.