+135-3858-6433 (GuangDong)
+188-1699-6168 (ShangHai)
+852-6957-5415 (HongKong)

TEKNOR APEX

APEX® 98-A0436F-80

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General		
Material Status	• Commercial: Active	
Availability	• Africa & Middle East • Asia Pacific	• Latin America • North America
Features	• Medium Gloss	
Uses	• Profiles	
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.	
Forms	• Pellets	

ASTM & ISO Properties [1]

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.35		ASTM D792
Mechanical	**Nominal Value**	**Unit**	**Test Method**
Tensile Strength (Break)	2480	psi	ASTM D638
Tensile Elongation (Break)	370	%	ASTM D638
Hardness	**Nominal Value**	**Unit**	**Test Method**
Durometer Hardness (Shore A, 15 sec)	80		ASTM D2240

Additional Information

Data Sheet Applies to Color(s) Listed Below:
Black 1 NP (1094163)

10/19 Core

Notes

[1] Typical properties: these are not to be construed as specifications.