



# Cycle-Tek 1080 Natural

Teknor Apex Company - Flexible Polyvinyl Chloride

## General Information

### General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Asia Pacific • Latin America • North America
Recycled Content	• Post-Industrial (PIR)/Pre-Consumer, 25%
Features	• Plasticized
Uses	• General Purpose
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Appearance	• Opaque
Forms	• Pellets
Processing Method	• Injection Molding

## ASTM & ISO Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.32		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2070	psi	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec, Hand Held)	80		ASTM D2240

### Additional Information

Data Sheet Applies to Color(s) Listed Below:

Natural (1005113)

2/2024 cw

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.