

**TEKNOR APEX CO**

505 CENTRAL AVE PO BOX 2290 PAWTUCKET RI 02861

Material Designation: **TB-6000-60**

Product Description: Thermoplastic Elastomer (TPE), designated "Tekbond" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.0-1.2	HB	-	-	50	50	50	-	-
<b>CTI:</b> -	<b>IEC CTI</b> (v): -	<b>HVTR:</b> -	<b>D495:</b> -			<b>IEC Ball Pressure</b> (° C): -			
<b>Dielectric Strength</b> (kV/mm): -		<b>Volume Resistivity</b> (10 <sup>10</sup> ohm-cm): -			<b>Dimensional Stability</b> (%): -				
<b>ISO Tensile Strength</b> (MPa): -		<b>ISO Flexural Strength</b> (MPa): -			<b>ISO Heat Deflection</b> (° C): -				
<b>ISO Tensile Impact</b> (kJ/m <sup>2</sup> ): -		<b>ISO Izod Impact</b> (kJ/m <sup>2</sup> ): -			<b>ISO Charpy Impact</b> (kJ/m <sup>2</sup> ): -				

Report Date: 3/30/2000

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.