

TEKNOR APEX CO

505 CENTRAL AVE PO BOX 2290 PAWTUCKET RI 02861

Material Designation: TB-6000-60

Product Description: Thermoplastic Elastomer (TPE), designated "Tekbond" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.0–1.2	HB	—	—	50	50	50	—	—
CTI: —	IEC CTI (V): —	HVTR: —	D495: —			IEC Ball Pressure (° C): —			
Dielectric Strength (kV/mm): —		Volume Resistivity (10 ⁹ ohm-cm): —			Dimensional Stability(%): —				
ISO Tensile Strength (MPa): —		ISO Flexural Strength (MPa): —			ISO Heat Deflection (° C): —				
ISO Tensile Impact (kJ/m²): —		ISO Izod Impact (kJ/m²): —			ISO Charpy Impact (kJ/m²): —				

Report Date: 3/30/2000

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.