+135-3858-6433 (GuangDong)
+188-1699-6168 (ShangHai)
+852-6957-5415 (HongKong)

TEKNOR APEX

# Telcar® GS7567

## Teknor Apex Asia Pacific PTE. LTD. - Thermoplastic Elastomer

### General Information

| General | |
|---|---|
| Material Status | • Commercial: Active |
| Availability | • Asia Pacific |
| Forms | • Pellets |

### ASTM & ISO Properties [1]

| Physical | Nominal Value | Unit | Test Method |
|---|---|---|---|
| Density / Specific Gravity | 1.30 | | ASTM D792 |
| Melt Mass-Flow Rate (MFR) (200°C/5.0 kg) | 13 | g/10 min | ASTM D1238 |
| **Elastomers** | **Nominal Value** | **Unit** | **Test Method** |
| Tensile Stress (100% Strain) | 580 | psi | ASTM D412 |
| Tensile Stress (300% Strain) | 725 | psi | ASTM D412 |
| Tensile Strength (Yield) | 2030 | psi | ASTM D412 |
| Tensile Elongation (Break) | 750 | % | ASTM D412 |
| **Hardness** | **Nominal Value** | **Unit** | **Test Method** |
| Durometer Hardness (Shore A, 10 sec) | 75 | | ASTM D2240 |
| **Flammability** | **Nominal Value** | **Unit** | **Test Method** |
| Flame Rating (0.06 in) | V-0 | | UL 94 |
| Oxygen Index | 24 | % | ASTM D2863 |

**Additional Information**

Item Code (Reference): 9508158

### Notes

[1] Typical properties: these are not to be construed as specifications.