+135-3858-6433 (GuangDong)
+188-1699-6168 (ShangHai)
+852-6957-5415 (HongKong)

TEKNOR APEX

Telcar® GS8567

Teknor Apex Asia Pacific PTE. LTD. - Thermoplastic Elastomer

General Information

General	
Material Status	• Commercial: Active
Availability	• Asia Pacific
Forms	• Pellets

ASTM & ISO Properties [1]

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.28		ASTM D792
Melt Mass-Flow Rate (MFR) (200°C/5.0 kg)	14	g/10 min	ASTM D1238
Elastomers	**Nominal Value**	**Unit**	**Test Method**
Tensile Stress (100% Strain)	580	psi	ASTM D412
Tensile Stress (300% Strain)	725	psi	ASTM D412
Tensile Strength (Yield)	1890	psi	ASTM D412
Tensile Elongation (Break)	700	%	ASTM D412
Hardness	**Nominal Value**	**Unit**	**Test Method**
Durometer Hardness (Shore A, 10 sec)	87		ASTM D2240
Flammability	**Nominal Value**	**Unit**	**Test Method**
Flame Rating (0.06 in)	V-0		UL 94
Oxygen Index	24	%	ASTM D2863

Additional Information

Item Code (Reference): 9507521

Notes

[1] Typical properties: these are not to be construed as specifications.