+135-3858-6433 (GuangDong) +188-1699-6168 (ShangHai) +852-6957-5415 (HongKong)



Terraloy™ MB-20001A

Teknor Apex Company - Thermoplastic Starch + Copolyester

General Information

Product Description

Terraloy MB-20001A is a Thermoplastics Starch/Biodegradable Copolyester masterbatch that contains up to 50% of TPS renewable content and is 100% biodegradable. Biodegradable Copolyester melt index in the masterbatch is 5. This compound is for blown film application as well as injection molded parts. Recommended letdown ratio between TPS and Biodegradable Copolyester is 60:40.

General					
Material Status	Commercial: Active				
Availability	 Africa & Middle East Asia Pacific	EuropeLatin America	North America		
Features	Biodegradable	Renewable Resource Content			
Uses	• Film				
Forms	• Pellets				
Processing Method	Blown Film				

ASTM & ISO Properties 1					
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.32		ASTM D792		
Melt Mass-Flow Rate (MFR) (210°C/2.16 kg)	2.1	g/10 min	ASTM D1238		
Biobased Content	< 50	%			
Thermal	Nominal Value	Unit	Test Method		
Peak Melting Temperature	248	°F	ASTM D3418		
Additional Information	Nominal Value	Unit			
Let Down Ratio - with Copolyester	60:40				

Notes

¹ Typical properties: these are not to be construed as specifications.