



组件 - 塑料
UL 档案号: E54709

TEKNOR APEX CO
505 CENTRAL AVE
PO BOX 2290
PAWTUCKET, RI 02861 United States



4139D

Ethylene Propylene Thermoplastic Rubber (EPTR), pellets

可燃性	值	测试方法
UL 阻燃等级		
1.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB	UL 94
3.0 mm, ALL	HB40	IEC 60695-11-10, -20
1.0 mm, ALL	HB75	IEC 60695-11-10, -20
电气性能	值	测试方法
热丝引燃 (HWI)		UL 746
1.0 mm	PLC 3	
3.0 mm	PLC 2	
高电弧燃烧指数(HAI)		UL 746
1.0 mm	PLC 0	
3.0 mm	PLC 0	
相比耐漏电起痕指数(CTI)	PLC 0	UL 746
高电压电弧起痕速率 (HVTR)	PLC 1	UL 746
耐电弧性	PLC 6	ASTM D495
热性能	值	测试方法
RTI Elec		UL 746
1.0 mm	100 °C	
3.0 mm	100 °C	
RTI Imp		UL 746
1.0 mm	100 °C	
3.0 mm	100 °C	
RTI		UL 746
1.0 mm	100 °C	
3.0 mm	100 °C	