

POLYPROPYLENE		CPPP	
PDCPPP2050CN		MELT INDEX	25
IMPACT COPOLYMER		IZOD	NB

Properties	ASTM		Typical Values
PHYSICAL			
Melt Index	D-1238	25g/10 min.	25.0
Density	D-1505	gm/cm ³	0.902
IMPACT			
Notched Izod Impact	D-256	ft-lb/in	No Break
MECHANICAL			
Tensile Strength @ Yield	D-638	psi	3,300
Tensile Elongation @ Yield		%	6.6
Flexural modulus	D-790A	psi	150,000
DTUL @ 66psi-Unannealed	D-648	°C	104

The information contained herein is based upon data believed to be reliable and relates only to the matters specifically contained herein. Although such information is, to the best of our knowledge and belief, accurate and reliable as of the date hereof, no representation, warranty (expressed or implied, of merchantability, fitness or otherwise), or guarantee is made as to the suitability, accuracy, reliability, or completeness of the information. It is the user's responsibility to satisfy itself as to the suitability, accuracy, reliability and completeness of such information for its particular use. There is no warranty against patent infringement, and PolyOne Distribution shall not be liable for any loss, damage, or injury that may occur from the use of this information. No statement herein shall be construed as an endorsement of any product or process.