

# Geon™ Vinyl Flexible XV3715 Flexible Polyvinyl Chloride

## **Key Characteristics**

General				
Material Status	Commercial: Active		_	
Regional Availability	<ul><li>Africa &amp; Middle East</li><li>Asia Pacific</li></ul>	<ul><li>Europe</li><li>Latin America</li></ul>	North America	
Features	<ul> <li>Food Contact Acceptable</li> </ul>			
Agency Ratings	<ul> <li>FDA Food Contact, Unspec</li> </ul>	cified Rating		
Appearance	<ul> <li>Clear/Transparent</li> </ul>			
Forms	• Pellets			
Processing Method	Extrusion	<ul> <li>Injection Molding</li> </ul>		

## Technical Properties 1

	• · · · · · · · · · · · · · · · · · · ·		
Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density / Specific Gravity	1.16	1.16	ASTM D792
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus <sup>2</sup>	427 psi	2.94 MPa	ASTM D638
Elastomers	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Strength <sup>3</sup> (Break)	1230 psi	8.48 MPa	ASTM D412A
Tensile Elongation <sup>3</sup> (Break)	490 %	490 %	ASTM D412A
Hardness	Typical Value (English)	Typical Value (SI)	Test Method
Durometer Hardness (Shore A, 10 sec)	48	48	ASTM D2240

Additional Information

NOTE: All ingredients used in the formulation of this compound are listed in the United States FDA Code of Federal Regulations, Title 21. The only restriction is that the plasticizer is "For foods of high water content only". This statement is only an overview of the FDA listings for this product. It is the customer's responsibility to ensure that the compound is suitable for its intended application.

Rev: 2013-12-12 Page: 1 of 2

<sup>&</sup>lt;sup>1</sup> Typical values are not to be construed as specifications.

<sup>&</sup>lt;sup>2</sup> Type IV, 20 in/min (510 mm/min)

<sup>&</sup>lt;sup>3</sup> 20 in/min (510 mm/min)