



Edgetek™ XT X XT 1000 Natural Copolyester

Key Characteristics

Product Description

Edgetek™ XT high performance blends offer outstanding strength, durability and chemical resistance through the combination of Eastman Tritan™ copolyester with other various polymeric resins. Edgetek™ XT blends made with Tritan™ copolyester are available in standard grades or can be customized to meet specific performance requirements.

General

Material Status	• Commercial: Active		
Regional Availability	• Africa & Middle East • Europe	• Latin America • North America	
Features	• BPA Free • Chemical Resistant • Cleanable	• Good Color Stability • Good Processability • Good Toughness	• High Impact Resistance • Hydrolytically Stable • Medium Heat Resistance
Uses	• Appliance Components • Appliances • Consumer Applications • Electrical Housing	• Household Goods • Housings • Industrial Applications • Kitchenware	• Medical Devices • Medical/Healthcare Applications
Forms	• Pellets		

Technical Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density / Specific Gravity	1.16	1.16	ASTM D792
Melt Mass-Flow Rate (MFR) (260°C/5.0 kg)	22 g/10 min	22 g/10 min	ASTM D1238
Molding Shrinkage - Flow (0.125 in (3.18 mm))	5.8E-3 in/in	0.58 %	ASTM D955
Molding Shrinkage - Across Flow (0.125 in (3.18 mm))	3.0E-3 in/in	0.30 %	ASTM D955
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus ²	226000 psi	1560 MPa	ASTM D638
Tensile Strength ³ (Yield)	5800 psi	40.0 MPa	ASTM D638
Tensile Strength ² (Break)	5300 psi	36.5 MPa	ASTM D638
Tensile Elongation ² (Break)	74 %	74 %	ASTM D638
Flexural Modulus ⁴	250000 psi	1720 MPa	ASTM D790
Flexural Strength ⁴	10500 psi	72.4 MPa	ASTM D790
Impact	Typical Value (English)	Typical Value (SI)	Test Method
Notched Izod Impact 73°F (23°C), 0.125 in (3.18 mm), Injection Molded	18 ft·lb/in	960 J/m	ASTM D256
Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Deflection Temperature Under Load 66 psi (0.45 MPa), Unannealed, 0.125 in (3.18 mm)	203 °F	95.0 °C	ASTM D648
Deflection Temperature Under Load 264 psi (1.8 MPa), Unannealed, 0.125 in (3.18 mm)	176 °F	80.0 °C	ASTM D648
CLTE - Flow (-22 to 86°F (-30 to 30°C))	3.9E-5 in/in/°F	7.1E-5 cm/cm/°C	ASTM D696

Copyright © 2019 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

Notes

¹ Typical values are not to be construed as specifications.

² Type I, 2.0 in/min (51 mm/min)

³ 2.0 in/min (51 mm/min)

⁴ 0.50 in/min (13 mm/min)

CONTACT INFORMATION**Americas**

United States - Avon Lake
+1 440 930 1000

United States - McHenry
+1 815 385 8500

Asia

China - Guangzhou
+86 20 8732 7260

China - Shenzhen
+86 755 2969 2888

China - Suzhou
+86 512 6823 24 38

China - Suzhou
+86 512 6265 2600

Hong Kong -
+852 2690 5332

Taiwan - Yonghe City,
+886 9396 99740, +886 2929 1849

Europe

Germany - Gaggenau
+49 7225 6802 0

Spain - Barbastro (Huesca)
+34 974 310 314



Beyond Polymers.

Better Business Solutions.™

www.polyone.com

PolyOne Americas

33587 Walker Road
Avon Lake, Ohio 44012
United States
+1 440 930 1000
+1 866 POLYONE

PolyOne Asia

No. 88 Guoshoujing Road
Z.J Hi-tech Park, Pudong
Shanghai, 201203, China
+86 21 5080 1188

PolyOne Europe

6 Giällewee
+352 269 050 35

Copyright ©, 2019 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.