



# Maxxam™ FR PE 112 Natural RoHS

## Low Density Polyethylene

### Key Characteristics

#### Product Description

Maxxam™ FR flame-retardant polyolefin compounds and masterbatches meet stringent flammability performance requirements defined by industry agencies, including Underwriters Laboratories UL 94 V-2, V-0, and 5VA performance ratings. In addition, many compounds in the Maxxam FR portfolio offer elevated Relative Thermal Index (RTI) ratings.

#### General

Material Status	• Commercial: Active
Regional Availability	• North America
Features	• Flame Retardant
Appearance	• Natural Color
Forms	• Pellets

### Technical Properties <sup>1</sup>

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Specific Gravity	0.970	0.970	ASTM D792
Specific Volume	28.3 in <sup>3</sup> /lb	1.02 cm <sup>3</sup> /g	ASTM D792
Melt Mass-Flow Rate (MFR) <sup>2</sup> (190°C/2.16 kg)	9.1 g/10 min	9.1 g/10 min	ASTM D1238
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Strength <sup>3</sup> (Yield)	1500 psi	10.3 MPa	ASTM D638
Tensile Elongation <sup>3</sup> (Break)	80 %	80 %	ASTM D638
Flammability	Typical Value (English)	Typical Value (SI)	Test Method
Flame Rating			UL 94
0.0625 in (1.59 mm), NC	V-2	V-2	
0.118 in (3.00 mm), NC	V-2	V-2	

#### Notes

<sup>1</sup> Typical values are not to be construed as specifications.

<sup>2</sup> Procedure A

<sup>3</sup> Type I, 2.0 in/min (51 mm/min)

**CONTACT INFORMATION****Americas**

Mexico - Toluca  
+52 722 2790200  
United States - Avon Lake  
+1 440 930 1000

**Asia**

China - Shanghai  
+86 21 5080 1188  
China - Shenzhen  
+86 755 2969 2888  
China - Suzhou  
+86 512 6823 24 38  
China - Tianjin  
+86 22 2532 8818  
India - Pune  
Japan - Tokyo  
+81-3-6261-3980  
Singapore - Singapore  
+65 6861 9325  
Taiwan - Yonghe City,  
+886 9396 99740, +886 2929 1849

**Europe**

Germany - Gaggenau  
+49 7225 6802 0  
Spain - Barbastro (Huesca)  
+34 974 310 314  
Turkey - Esenyurt - Istanbul – Turkey  
+90 212 549 2256



*Beyond Polymers.*

*Better Business Solutions. SM*

[www.polyone.com](http://www.polyone.com)

**PolyOne Americas**

33587 Walker Road  
Avon Lake, Ohio 44012  
United States  
+1 440 930 1000  
+1 866 POLYONE

**PolyOne Asia**

No. 88 Guoshoujing Road  
Z.J Hi-tech Park, Pudong  
Shanghai, 201203, China  
+86 21 5080 1188

**PolyOne Europe**

6 Giallewee  
+352 269 050 35

Copyright ©, 2015 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.