



Nymax™ X GMF 604 40 UV Black 148 rev 4

Polyamide 6

Key Characteristics

Product Description

The Nymax® GMF 600 Series of compounds are based upon nylon 6 resins and select combinations of glass fiber and mineral reinforcements offering a unique balance of physical property and part performance. These materials have been specifically formulated to offer ease of processing in most standard thermoplastic processing equipment.

General

Material Status	• Commercial: Active
Regional Availability	• Latin America • North America
Filler / Reinforcement	• Glass\Mineral, 40% Filler by Weight
Additive	• Heat Stabilizer • UV Stabilizer
Features	• General Purpose • Heat Stabilized
Uses	• Automotive Applications • Consumer Applications • Industrial Applications • Construction Applications • General Purpose
Automotive Specifications	• CHRYSLER MS-DB-41 CPN3916
Appearance	• Black
Forms	• Pellets
Processing Method	• Injection Molding

Technical Properties ¹

Physical	Typical Value (English)	Typical Value (SI)	Test Method
Density / Specific Gravity	1.48	1.48	ASTM D792
Density	1.49 g/cm ³	1.49 g/cm ³	ISO 1183
Molding Shrinkage - Flow	2.0E-3 to 4.0E-3 in/in	0.20 to 0.40 %	ASTM D955
Molding Shrinkage	0.20 to 0.30 %	0.20 to 0.30 %	ISO 294-4
Water Absorption (24 hr, 0.125 in (3.18 mm))	0.80 %	0.80 %	ASTM D570
Water Absorption (24 hr, 73°F (23°C))	1.0 %	1.0 %	ISO 62
Mechanical	Typical Value (English)	Typical Value (SI)	Test Method
Tensile Modulus	1.20E+6 psi	8270 MPa	ASTM D638
Tensile Modulus	1.23E+6 psi	8500 MPa	ISO 527-2
Tensile Strength ² (Yield)	17500 psi	121 MPa	ASTM D638
Tensile Stress (Yield)	17000 psi	117 MPa	ISO 527-2
Tensile Strength ² (Break)	17000 psi	117 MPa	ASTM D638
Tensile Elongation ² (Break)	2.0 to 3.0 %	2.0 to 3.0 %	ASTM D638
Tensile Strain (Break)	2.5 %	2.5 %	ISO 527-2
Flexural Modulus	1.10E+6 psi	7580 MPa	ASTM D790
Flexural Modulus	1.22E+6 psi	8400 MPa	ISO 178
Flexural Strength	26000 psi	179 MPa	ASTM D790
Flexural Stress	27600 psi	190 MPa	ISO 178
Impact	Typical Value (English)	Typical Value (SI)	Test Method
Notched Izod Impact			ASTM D256A
73°F (23°C), 0.125 in (3.18 mm), Injection Molded	1.3 ft·lb/in	69 J/m	
Notched Izod Impact Strength	6.0 ft·lb/in ²	13 kJ/m ²	ISO 180

Copyright © 2019 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.

Thermal	Typical Value (English)	Typical Value (SI)	Test Method
Heat Deflection Temperature 264 psi (1.8 MPa), Annealed	383 °F	195 °C	ISO 75-2/A
Additional Information			
Molded Test Bars: Dry as Molded			

Processing Information

Injection	Typical Value (English)	Typical Value (SI)
Drying Temperature	180 °F	82 °C
Drying Time	4.0 hr	4.0 hr
Suggested Max Moisture	0.10 to 0.20 %	0.10 to 0.20 %
Rear Temperature	500 to 530 °F	260 to 277 °C
Middle Temperature	525 to 550 °F	274 to 288 °C
Front Temperature	525 to 550 °F	274 to 288 °C
Nozzle Temperature	525 to 550 °F	274 to 288 °C
Mold Temperature	120 to 200 °F	49 to 93 °C

Notes

¹ Typical values are not to be construed as specifications.

² Type I, 0.20 in/min (5.1 mm/min)

CONTACT INFORMATION

Americas

United States - Avon Lake
+1 440 930 1000

United States - McHenry
+1 815 385 8500

Asia

China - Guangzhou
+86 20 8732 7260

China - Shenzhen
+86 755 2969 2888

China - Suzhou
+86 512 6823 24 38

China - Suzhou
+86 512 6265 2600

Hong Kong -
+852 2690 5332

Taiwan - Yonghe City,
+886 9396 99740, +886 2929 1849

Europe

Germany - Gaggenau
+49 7225 6802 0

Spain - Barbastro (Huesca)
+34 974 310 314



Beyond Polymers.

Better Business Solutions. SM

www.polyone.com

PolyOne Americas

33587 Walker Road
Avon Lake, Ohio 44012
United States
+1 440 930 1000
+1 866 POLYONE

PolyOne Asia

No. 88 Guoshoujing Road
Z.J Hi-tech Park, Pudong
Shanghai, 201203, China
+86 21 5080 1188

PolyOne Europe

6 Giallewee
+352 269 050 35

Copyright ©, 2019 PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the Information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the Information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the Information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the Information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the Information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the Information or products reflected by the Information. This data sheet shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.